

ANGLE	± 5°	REV	LOCAS	DESCRIPTION	DESIGN	DATE	卫国峰
X.XXX	± 0.05	01			DRAWN	DATE	尚伟
X.XX	± 0.15	02			CHECKED	DATE	吴汉学
X.X	± 0.25	03			AUDITED	DATE	龚劲松
X	± 0.50	04			APPROVED	DATE	eric

Specifications/备注 (Remark)

1-材料 (MATERIAL)

胶芯: PPS+30%G. UL94V-0, 颜色: 黑色
 Housing: PPS+30%G. UL94V-0, Color: Black
 端子: 黄铜

Contact: Brass CuZn 36Pb3 (C3600)

相配针: ϕ 0.47mm

Connecting Pin: ϕ 0.47mm

2-特性 (characteristics):

额定电流: 3.00 AMP


Raring Current: 3.00 AMP .

接触阻抗: 10m Ω MAX.

Contact Resistance: 10m Ω MAX .



绝缘阻抗: 1000M Ω MIN.

Insulating Resistance: 1000M Ω MIN.



Stright socket connector:solder tail
 single row
 Availability from:2 to 40 contacts
 Standard number of contacts 40

ORDERING INFORMATION R1528-X XX X X G S 100 1



Stright socket connector:solder tail
 double row
 Availability from:4 to 80 contacts
 Standard number of contacts 80

YLIES 东莞市瑞翔精密连接器有限公司
 DONG GUAN YLIES PRECISE CONNECTOR CO.,LTD

Tel:0769-85381995 / Fax:0769-85493987 / Email: ylies@ylies.cn / Web:www.ylies.cn

TITLE 248-2.0mm 圆孔排针 180度 DATE 2018-02-18

PROJECTON REV A UNIT mm SCALE 1:1 PAGE 1/1

PART NO: 2.0mm 圆孔排针 180度 DRAWING NO: